# Top-V

# Fan light systems for bottom and top hung windows



## DESCRIPTION

Powerfull surface-mounted remote control system Top-V for bottom and top hung windows with **elegant design assures the tightness** of the window.

#### CHARACTERISTICS

- All types are suitable for installation on aluminium, PVC or timber windows.
- There is a set available for all window types: straight window, sloping head window, round and arched window, if desired in combination with a sill transmission. A set is also available for an additional bottom and top hung window installed side by side or one above the other.
- All parts of the remote control system are manufactured from non-corroding materials.
- Finish:
  - Handle, link arm and cover sections in aluminium anodised or polyester powder coated in a choice of more than 450 RAL colours.
  - The U-shaped cover sections are available in lengths of 3 or 6 m.
  - Rods in aluminium anodised, steel zinc plated or stainless steel and available in lengths of 1, 2 or 3 m.
- To get around sills, there is a flexible sill transmission with cable or a sill transmission with bar available.
- Operating devices:
  - handle
  - fixed winder, with horizontal or vertical winding gear
  - loose winder, with horizontal or vertical winding gear

#### BOTTUM HUNG WINDOWS

- All types are non-handed.
- Size ranges:
  - straight windows
    - ◊ vent width: 400-3600 mm
    - ◊ vent height: 250-1800 mm
  - sloping head windows (0 to 50°)
    - ◊ vent width: 400-1200 mm
    - ◊ vent height: 250-1200 mm
  - round and arched windows (up to 1200 mm wide)
    - ◊ vent width: 400-1200 mm
    - ◊ vent height: 250-1200 mm
  - windows installed side by side
  - windows installed one above the other
- Total vent weight: max. 80 kg
- Opening: 170 mm (120 mm for Fh = 250-400 mm)

### TOP HUNG WINDOWS

- Top hung windows should be specified whether the operating device is placed on the right (supplied as standard) or left.
- Size ranges:
  - straight windows
  - windows installed side by side
  - windows installed one above the other
- Size range:
  - vent width: 400-3600 mm
  - vent height: 250-1200 mm
  - total vent weight: max. 80 kg
  - opening: 170 mm (120 mm for Fh = 250-400 mm)













Waregemstraat 5 - 9870 Zulte - Belgium commercial@sobinco.com T +32 9 388 88 81 - F +32 9 388 88 21 www.sobinco.com